

Payment Terminal "Gaga-Go" 885



885



885

AUSFÜHRUNG

- + Kompakter EVM kontaktlos Bezahleser mit vielen Erweiterungen
- + Einfache Integration, platzsparender Einsatz und eine hohe Flexibilität bei der Auswahl der Funktechnologie
- + Unterstützt die gängigsten RFID Kartenstandards der Frequenz 13,56 MHz sowie die ISO-Standards ISO 14443, ISO 15693 und ISO 18092
- + Integriertes Farbdisplay (optional)
- + RS232 und USB Schnittstelle
- + Anpassungen nach kunden-spezifischen Anforderungen möglich

CONSTRUCTION

- + Compact EMV contactless payment reader with many extensions
- + Easy integration, space-saving use and high flexibility in the choice of RFID technology
- + Supports the most common RFID card standards of the frequency 13.56 MHz as well as the ISO standards ISO 14443, ISO 15693 and ISO 18092
- + Integrated color display (optional)
- + RS232 and USB interface
- + Customization according to customer specific requirements possible

ABMESSUNGEN

72 x 60 x 21,1 mm

DIMENSIONS

72 x 60 x 21,1 mm



VISA DISCOVER



MECHANISCHE KENNWERTE | MECHANICAL CHARACTERISTICS

ALLGEMEIN GENERAL	Gewicht Brandklasse	150 g UL 94 V0	Weight Flame rating
----------------------	------------------------	-------------------	------------------------

ELEKTRISCHE DATEN | ELECTRICAL DATA

ALLGEMEIN GENERAL	Versorgungsspannung	5-24V (RS232) 5V (USB)	Power requirements
	Leistungsaufnahme	max. 4,5W	Current consumption

SCHNITTSTELLEN INTERFACES

RS232 | max. 921,6k Baud
USB 2.0 Type C
TCP / IP over RS232 (SLIP)

Extension board with: SPI / I²C/ Ethernet / MDB / LTE /
WiFi / Bluetooth/ 4x SAM /Linux

RFID	Frequenz Antenne	13.56 MHz Integrated Antenna	Frequency Antenna
------	---------------------	---------------------------------	----------------------

DISPLAY (optional)

Display Type	2.0 Zoll / inch	Display type
Bildschirmfarbe	TFT IPS	Display color
Helligkeit	Colors 262K	Brightness
Auflösung	500 cd /m ² 320 x 240	

AUDIO	Summer	Integrated multiy-frequency	Buzzer
-------	--------	-----------------------------	--------

UMGEBUNGSBEDINGUNGEN | ENVIRONMENTAL CONDITIONS

KLIMATISCHE BEDINGUNGEN	Lagertemperatur Betriebstemperatur	- 30°C ... + 70°C - 25°C ... + 60°C (with Display +60°C....-20 °C)	Storage temperature Operating temperature
CLIMATIC CONDITIONS	Luftfeuchtigkeit (relativ) Luftdruck	10 ... 90% (non-condensing) 70 ... 106 kPa	Humidity (relative) Air pressure

RFID PROTOKOLLE | RFID PROTOCOLS

ISO 14443 A	MIFARE CLASSIC MIFARE Mini MIFARE DESFire MIFARE DESFire Light MIFARE Ultralight
ISO 14443 B	Calypso
ISO 15693	iCODE

CERTIFIED PAYMENT CARDS	VISA payWave Mastercard Contactless American Express Discover Additional kernels available (optional)
----------------------------	---

PAYMENT APPLICATION	SDK provided for custom payment application development Optionally provided by ddm: nexo Payment Application
---------------------	---

Certification	EMV Level 1 EMV Level 2 PCI PTS 7.x SRED FCC CE RoHS
---------------	---

Anschrift | Address

Firma:
Company:Datum:
Date:Adresse:
Address:Tel.:
Phone:Name:
Name:Fax:
Fax:Kundenr.:
Customer No.:E-Mail:
E-Mail:

Bestellschlüssel | ordering code

Muster und 3D-Daten | Samples and 3D Data

Bitte nutzen Sie die nebenstehenden Links und QR-Codes, um Ihre individuellen Muster und 3D-Daten anzufordern.

www.hopt-schuler.comsales@hopt-schuler.com

Please use the links and QR-codes beside to require your specific samples and 3D Data.